



Portable Test Equipment

**TS22®
Amplified Speaker
Test Set**

*work with both
hands free*

The TS22 test set works under many conditions, in different environments and with a variety of systems. An internal amplified speaker enables field technicians to continue working with both hands free while waiting for callbacks or assistance after being put on hold. Ruggedness, versatility and reliability best describe the features of this butt-in type test set. Many features have been built into the TS22 test set adding to its reliability while keeping it lightweight and compact.

Features:

- Internal amplified speaker
- Tone (DTMF) and pulse operation
- Last number redial
- DTMF signal levels compensated for loop length
- RainSafe™ test set for use in extreme weather conditions
- Audible electronic ringer
- 3-year redial storage time
- Field replaceable belt clip
- DropSafe™ unit up to 20 feet
- Continuous polarity LED indications
- Stores nine 18-digit numbers in repertory dialer (speed dialing)
- PBX pause button

Part Numbers:

- TS22 with Standard Angled Piercing Pin Clips CordP/N 22800-001
- TS22 with 346A Plug CordP/N 22800-004
- TS22 with Ground Start CordP/N 22800-007
- TS22 with 346A Plug and 1500 Ohm Resistor/Switch Cord.....P/N 22800-008
- TS22 with Angled Bed-of-Nails CordP/N 22800-009



Communications Products Division
809 Calle Plano, Camarillo, CA
93012-8519 USA
www.harris.com
1-800-437-2266 or 1-805-987-9511

PB No. 3010 4/99

TS22 is a registered trademark of Harris Corporation. RainSafe and DropSafe are trademarks of Harris Corporation. All other trademarks belong to their respective companies.

© 1999 HARRIS CORPORATION

next level solutions

