



Test Set Comparison Table

							
	TS®44DLX	TS®42DLX	TS®22A	TS®22	TS®25D	TS®30	TS®19
Extended range high-impedance DataSafe® operation in monitor mode	•	•			•		
High-impedance DataSafe® operation in monitor mode	•	•	•		•	•	•
Data lockout protection	•				•		
Data lockout override	•				•		
DSL/POTS filtering technology	•	•			•		
Low/high voltage indication	•	•			•		
Low current (mA) indication	•	•			•		
Over voltage protection	•	•	•	•	•	•	
Over current protection	•	•	•	•	•	•	
Two-way speakerphone for true hands-free conversations	•	•	•				
One-way amplified speaker for hands-free monitoring	•	•	•	•	•		
Audible ringer for callbacks	•	•	•	•	•	•	•
Waterproof – exceeds American Military Spec. MIL-STD-810E*	•	•					
RainSafe™ – safe in severe weather conditions	•	•	•	•		•	
DropSafe™ – passes 20 foot drop test onto concrete	•	•	•	•		•	
Meets Bellcore specifications	•	•	•	•		•	
Tone and pulse operation	•	•	•	•	•	•	•
Polarity indication in talk mode	•	•	•	•	•	•	•
PBX pause button	•	•	•	•	•		
Stores nine 18-digit numbers in repertory dialer (speed dialing)	•	•	•	•	•		
Replaceable 9V battery for powering speaker	•	•	•	•	•		

For more product information, visit www.flukenetworks.com